

enatel

# 860W 48V Rectifier



# RM848HE 110/230V

RECTIFIER  


DC OUT  
**48V**

MAX OUTPUT  
**860W**

## Key Features

- High Efficiency energy saving
- Universal AC input with metering
- Forced-air cooled
- Thermally protected
- Power factor corrected
- Input/output voltage and current protected

## Small & Powerful

If power density, efficiency and reliability are required, the RM848HE rectifier is just right for the job.

The building block of the MicroCOMPACT series, this modular rack-mounted rectifier boasts integrated AC metering, a robust universal AC input, high efficiency and a quality high power DC output. And it's fully backwards compatible, making the expansion or updating of installed microCOMPACTs completely seamless.

But it's tough too. Built to exacting New Zealand manufacturing and process integrity standards, the RM848HE maximises reliability based on a proven conversion topology that uses only the highest specification components. Designed to meet the energy demands of ICT applications and growing telecommunications networks, where it can offer unrivalled power densities and flexibility, it's been built to last.

This rectifier allows for the mounting of up to three power modules, a smart controller and DC distribution all in a 1RU x 19" front connect system supporting ETSI 300 deep enclosures, while its 'plug and play' design means installation and performance are unsurpassed.



# RM848HE Specifications



ELECTRICAL	RM848HE 110V	RM848HE 230V
<b>AC INPUT RATINGS</b>		
NOMINAL VOLTAGE:	110V AC	230V AC
INPUT VOLTAGE RANGE:	85-175V AC (reduced power below 100V AC)	85-300V AC (reduced power below 175V AC)
POWER FACTOR:	>0.99	
PEAK EFFICIENCY:	>93.0%	>95.0%
<b>DC OUTPUT RATINGS</b>		
NOMINAL VOLTAGE:	48V DC	
VOLTAGE RANGE:	43-60V	
MAXIMUM OUTPUT CURRENT:	12.5A	17.9A
OUTPUT POWER:	600W	860W
<b>ENVIRONMENTAL REQUIREMENTS</b>		
AMBIENT TEMPERATURE:	-20°C to 75°C [-4°F to 167°F] (maximum output power is derated above 45°C [113°F])	
<b>COMPLIANCES</b>		
SAFETY:	EN 62368-1	
IMMUNITY:	CISPR24	
EMISSIONS:	CISPR32	
AC HARMONICS:	EN 61000-3-2	
AC FLICKER AND FLUCTUATION:	EN 61000-3-3	
OTHER:	CE & RoHS Compliant	
<b>MECHANICAL</b>		
DIMENSIONS:	WIDTH:	55.0 mm [2.17 in]
	HEIGHT:	44.45 mm [1.75 in] (1U)
	DEEP:	260.0 mm [10.24 in] overall (rack depth 245.0 mm [9.65 in])
WEIGHT:	635 g [1.4 lb]	
COOLING:	Forced-air cooled (front to back airflow)	

Due to product development, specifications are subject to change without prior notice.  
 Pictures may be representative: actual products may differ.

